

FOW

1.32

τοοι

the NEW Fowler Mobile Tech Center! see page 55

<u> - A - T H O N</u>

1.COM

Volume 14.2



Fowler/Bowers XTH Holematic Pistol Grip range of bore gages offer extended travel with fixed anvils. The pistol grip handle incorporates a constant measuring pressure to eliminate operator "feel."



#### Fastest Measuring System! Ergonomic Design! Amazing Repeatability!

- · Large easy-to-read swivel display
- · Self centering heads
- RS-232C output and USB connectivity
- Three preset memories
- Fixed anvils

er TOOL-A-THON

- Resolution: .00005" /.001mm
- Range .080"-12" (2-300mm)
- Tungsten carbide measuring faces on all 3-point heads from .5" (12.5mm) and up.
- · Heads with special anvils available for threads, splines, slots, etc.
- Sizes over .500" (12.5mm) feature blind bore capability
- · Setting rings included in all sets
- · Includes UKAS certificates for all pistol grip, heads and rings
- · Special anvils available

#### Contact the Fowler Technical Department for special anvil applications.









Electronic Holematic Pistol Grip XTH - Individual sizes (includes pistol grip, head and ring)					
Order Number	Range	Accuracy	Depth	List Price	Sale Price
		2-Point Heads			
A54-566-701	.080"100" (2-2.5mm)	.00015" (0.004mm)	.350" (9mm)	\$2841.00	\$2272.80
A54-566-702	.100"120" (2.5-3mm)	.00015" (0.004mm)	.350" (9mm)	2841.00	2272.80
A54-566-703	.120"160" (3-4mm)	.00015" (0.004mm)	.470" (12mm)	2841.00	2272.80
A54-566-704	.160"200" (4-5mm)	.00015" (0.004mm)	.700" (18mm)	2841.00	2272.80
A54-566-705	.200"250" (5-6mm)	.00015" (0.004mm)	.700" (18mm)	2841.00	2272.80
		3-Point Heads			
A54-566-706	.250"312" (6-8mm)	.00015" (0.004mm)	2.28" (58mm)	\$2070.00	\$1656.00
A54-566-708	.312"375" (8-10mm)	.00015" (0.004mm)	2.28" (58mm)	2036.00	1628.80
A54-566-710	.375"500" (10-12.5mm)	.00015" (0.004mm)	2.28" (58mm)	2144.00	1715.20
A54-566-712	.500"625" (12.5-16mm)	.00015" (0.004mm)	2.44" (62mm)	2172.00	1737.60
A54-566-716	.625"750" (16-20mm)	.00015" (0.004mm)	2.44" (62mm)	2302.00	1841.60
A54-566-720	.750"-1" (20-25mm)	.00015" (0.004mm)	2.62" (66mm)	2467.00	1973.60
A54-566-725	1-1.375" (25-35mm)	.00015" (0.004mm)	2.62" (66mm)	2915.00	2332.00
A54-566-735	1.375"-2" (35-50mm)	.00015" (0.004mm)	3.15" (80mm)	2739.00	2191.20
A54-566-740	2-2.625" (50-65mm)	.00020" (0.005mm)	3.15" (80mm)	2807.00	2245.60
A54-566-745	2.625"-3.250" (65-80mm)	.00020" (0.005mm)	3.15" (80mm)	2807.00	2245.60
A54-566-750	3.250"-4" (80-100mm)	.00020" (0.005mm)	3.35" (85mm)	2989.00	2391.20
A54-566-800	4-5" (100-125mm)	.00025" (0.006mm)	3.94" (100mm)	3131.00	2504.80
A54-566-825	5-6" (125-150mm)	.00025" (0.006mm)	3.94" (100mm)	3323.00	2658.40
A54-566-850	6-7" (150-175mm)	.00030" (0.007mm)	3.94" (100mm)	3527.00	2821.60
A54-566-875	7-8" (175-200mm)	.00030" (0.007mm)	3.94" (100mm)	3669.00	2935.20
A54-566-876	8-9" (200-225mm)	.00030" (0.008mm)	3.94" (100mm)	4673.00	3738.40
A54-566-877	9-10" (225-250mm)	.00030" (0.008mm)	4.05" (103mm)	5160.00	4128.00
A54-566-878	10-11" (250-275mm)	.00035" (0.009mm)	4.05" (103mm)	5342.00	4273.60
A54-566-879	11-12" (275-300mm)	.00035" (0.009mm)	4.05" (103mm)	5897.00	4717.60

# Extra Handles 25% off

#### Holematic XTH Pistol Grip Only

Order Number	Range	List Price	Sale Price
A54-556-350	.080"250" (2-6mm)	\$1951.00	\$1450.00
A54-556-375	.250"750" (6-20mm)	1951.00	1450.00
A54-556-400	.750"-4" (20-100mm)	1951.00	1450.00
A54-556-480	4"-12" (100-300mm)	1951.00	1450.00
	````		

## **Bowers XTH Holematic Pistol Grip Sets**









#### Complete Range Sets

Order Number	Range	Includes	List Price	Sale Price
A54-566-009	.080"250" (2-6mm)	5 heads, 1 handle, 3 rings	\$6431.00	\$5144.00
A54-566-010	.250"375" (6-10mm)	2 heads, 1 handle, 1 ring	2524.00	2019.00
A54-566-020	.375"750" (10-20mm)	3 heads, 1 handle, 2 rings	2977.00	2381.00
A54-566-050	.750"-2" (20-50mm)	3 heads, 1 handle, 2 rings	3901.00	3120.00
A54-566-100	2-4" (50-100mm)	3 heads, 1 handle, 2 rings	4321.00	3456.00
A54-566-105	4-6" (100-150mm)	2 heads, 1 handle, 1 ring	3901.00	3120.00
A54-566-110	6-8" (150-200mm)	2 heads, 1 handle, 1 ring	5212.00	4169.00
A54-566-200	4-8" (100-200mm)	4 heads, 1 handle, 2 rings	8352.00	6681.00
A54-566-210	.750"-4" (20-100mm)	6 heads, 1 handle, 4 rings	6431.00	5144.00
A54-566-620	.250"750" (6-20mm)	5 heads, 1 handle, 3 rings	3589.00	2871.00
Connectivity Kit	s			
Order Number	Description			
A54-115-444	RS232 Power Computer Cor	nnect Kit	157.00	
A54-115-528	USB Power Computer Conne	ect Kit	220.00	
A54-100-350	CR2032 Battery		5.50	

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

3

-A-THON



4



X-PROOF HOT SPO

**BEST VALUE!** 

IP54 Shockproof indicator available!

X-Proof Gage Stand

Stand features:

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

5

/olume '

#### X-TENDED RANGE Pin Gage Sets Minus and Plus Tolerances

Ideal for checking hole size, location, gage slots, distance between holes, go/no-go gaging and setting other gages and micrometers.



Two ranges in one set! .011" —.060" & .061" —.250

#### Features:

Volume 14.2

- Class ZZ Black oxide finish offers extra protection against corrosion and rust, promotes
- longer life, and highlights wear trends that enables calibration to be performed more effectively
- · 240 pcs
- · Range: 0.011" 0.250" in .001" increments.
- · Set includes 2 handles and our X-Glide all purpose teflon lubricant
- Certificate of accuracy traceable to N.I.S.T. and registered ISO 9001

Order Number	Description	Accuracy	List Price	Sale Price
A53-880-823	NEW Plus Pin Gage Set	+0.0002"-0.0000"	\$229.95	\$209.95
A53-880-833	NEW Minus Pin Gage Set	+0.0000"-0.0002"	229.95	209.95

## **Pin Gage Handles**



- 8 sizes cover a full range of pin gages (.011" 1.0")
- · Color coded handle for GO, NO/GO applications
- · Both handle and collets are made of aluminum for pin protection
- · Collets are spring loaded and self-centering

Order Number	Description	List Price	Sale Price
A53-885-000	<b>NEW</b> .011"—.060"	\$17.00	\$14.50
A53-885-001	<b>NEW</b> .061"—.250"	20.00	16.50
A53-885-002	<b>NEW</b> .251"—.500"	23.50	20.50
A53-885-003	<b>NEW</b> .501"—.625"	27.00	24.00
A53-885-004	<b>NEW</b> .626"—.750"	33.00	30.00
A53-885-005	<b>NEW</b> .751"—.832"	36.00	33.00
A53-885-006	<b>NEW</b> .833"—.916"	40.00	37.00
A53-885-007	<b>NEW</b> .917"—1.0"	45.00	41.00
A53-885-008	<b>NEW</b> All Sizes .011"—1.0"	230.00	210.00

XTRA MAG Mag Base Micrometer Stand

- NEW Micrometer shown not included.
- · Holds standard 0-12" micrometers firmly to metal surfaces
- · Use at machine centers, work, assembly and
- inspection stations, steel tables and shelves
  - · V-bottom for mounting on cylindrical surfaces
  - On/Off magnet switch
  - Blue enamel finish
  - Base is 2.30" L x 1.20" W x 3.50" H

	Price Sale Price	4
A52-247-010 NEW Xtra-Mag Base Micrometer Stand \$	48.50 <b>\$40.00</b>	,

## **Adjustable Micrometer Stand**



A compact, well-constructed, folding micrometer stand with a unique locking mechanism that positions the micrometer over a 180° range for perfect use and viewing.

FREE!

Ball Attachment

FREE!

Ball Attachment

Order Number	Description	List Price	Sale Price
A52-247-005	Micrometer Stand	\$33 <mark>.05</mark>	\$23.50

## XTRA-VALUE II Electronic Micrometers X-SERIES

- · Jet black, grey enamel finish
- · Large LCD display.
- Resolution: .00005"/.001mm
- Accuracy: ±.00016"/.004mm (up to 2")
- Direct RS-232 output
- · Carbide measuring faces.
- Absolute and incremental modes
- Ratchet thimble
- · Includes shop hardened case

Order Number	Description	Range	List Price	Sale Price
A54-870-001	Xtra-Value II Electronic Micrometer	0-1"/0-25mm	\$84.00	\$59.50
A54-870-002	Xtra-Value II Electronic Micrometer	1-2"/25-50mm	85.00	75.40
A54-870-003	Xtra-Value II Electronic Micrometer	2-3"/50-75mm	99.95	89.80
A54-870-103	Xtra-Value II Electronic Micrometer Set	0-3"/0-75mm	300.00	183.00
A54-100-350	CR2032 Battery		5.50	

Fowler

0-1" 0.00005"

## **Electronic Coolant Resistant Micrometers**

- Protected to IP54 specifications
- Large LCD Display
- Automatic switch off
- Resolution: .00005"/.001mm
- Direct RS-232 output
- · Carbide measuring faces
- Absolute & incremental modes
- Sizes over 1"/25mm include standard

Order Number	Description	Range	List Price	Sale Price
A54-860-001-1	IP54 Electronic Micrometer	0—1"/0 <mark>—25mm</mark>	\$106.40	\$79.20
A54-860-002-1	IP54 Electronic Micrometer	1—2"/2 <mark>5mm—50mm</mark>	123.20	89.20
A54-860-003-1	IP54 Electronic Micrometer	2—3"/5 <mark>0mm—75mm</mark>	134.40	99.80
A54-860-103-1	IP54 Electronic Micrometer Set	0—3"/0 <mark>—75mm</mark>	370.65	259.70
A54-902-110	LR44 Battery		6.60	

Fowler

0-1" 0. 00005"

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

RESISTAN

'olume '

Protected to:

TOOL-A-THON

## **Universal Electronic Micrometers**



111			" include stan ceeds Federal	
	Order no.	Range	List Price	S
	A52-229-201	0-1"	\$39.15	
	A52-229-202	1-2"	45.85	
	A52-229-203	2-3"	56.55	

A52-229-204

A52-229-205

A52-229-206

## **Digit Counter Micrometer**

я

Fowler

0-1" 0.0001

- · Digital counter reads to .001".
- Resolution: .0001" (using vernier)
- Microfine graduations on satin chrome

64.90

80.10

94.10

\$23.50 31.25

36.40

41.30

48.60

59.80

- Carbide tipped measuring faces
- · Positive locking nut on spindle
- · Sizes over 1" include standard
- Includes case

3-4"

4-5

5-6"

Order no.	Range	List Price	Sale Price
A52-224-001	0-1"	\$88.40	\$43.50
A52-224-002	1-2"	92.90	55.25
A52-224-003	2-3"	105.85	61.30
A52-224-004	3-4"	116.40	67.00

## Micrometer Calibration Set is available on page 35!

8

#### **Micrometer Set and Caliper Combo** 0-4" Micrometer Set Features: .0001" reading Carbide measuring faces A52-229-012 Combo Set Shown · Ratchet thimble and locking nut Microfine graduations Sizes over 1" include standard · Meets or exceeds Federal specifications NEW! 6" and 12" Dial Caliper Features: 4-way measuring Solid stainless steel construction Silky smooth movement throughout .100" range per revolution .001" reading dial face Tough shockproof design · Supplied in shop-hardened case Order Number Description List Price Sale Price A52-229-007 NEW 0-4" Micrometer Set and 6" Caliper \$271.65 \$220.00 A52-229-012 NEW 0-4" Micrometer Set and 12" Caliper 379.00 299.00 **Economy Micrometer Sets** .0001" reading (.01mm on metric set) · Carbide measuring faces · Ratchet thimble and locking nut Microfine graduations Sizes over 1" include standard Meets or exceeds Federal specifications Complete in a "Shop Hardened" molded case! Order Number List Price Sale Price Range \$141.10 A52-229-213 0-3" set \$99,50 0-4" set A52-229-214 217.30 121.50 0-100mm set A52-229-220 217.30 121.50 **Digit Counter Micrometer Sets** · Digital counter reads to .001". Resolution: .0001" (.01mm on metric set) Microfine graduations on satin chrome. · Carbide tipped measuring faces Ratchet thimble · Positive locking nut on spindle · Sizes over 1" supplied with standards

#### Complete in a "Shop Hardened" molded case!

Order Number	Range	List Price	Sale Price
A52-224-103	0-3" set	\$294.00	\$182.00
A52-224-104	0-4" set	399.85	201.80
A52-224-220	0-75mm set	294.00	201.80

9

/olume

TOOL-A-THON

## **12 piece Outside Inch Micrometer Set**



Fowler micrometers are of the finest quality available, at prices that defy competition. Special care in design and workmanship create a long lasting precision tool.

#### Features:

- Hammertone blue baked enamel finish
- · Microfine graduations on satin chrome finish and carbide tipped measuring faces
- · Diameter of measuring faces: .256"
- · Graduation: .0001"
- Flatness: .00003"
- · Quick, easy zero adjustment on sleeve
- · Positive lever locking clamp
- Spindle thread hardened, ground and lapped for ultimate accuracy
- Anvil & spindle hardened and precision ground with microlap finish on tips
- Meets or exceeds Federal accuracy specs
- Includes adjustment wrenches and fitted wooden case for all 12 micrometers

# NEW!

## All in a fitted wooden case!

Order Number	Description	List Price	Sale Price
A52-215-012-1	NEW 0-12" Micrometer Set	\$891.50	\$578.00

Poly-Cal	<sup>®</sup> Electronic Calipe	r Inch/Metric/Fra	iction	
Long		Range 6"/150mm     Polycarbonate frame		
1 18	and the second s	Large easy-to-read dis     Resolution .0005"/.01r	nm l	
	Polycarbonate Caliper	(Fractions by 1/64" ind • Absolute/Incremental	crements) Measurement	2
	• Fractional Measurement	<ul> <li>Direct inch/metric/fract</li> </ul>		
	Fractional Integration of the second se	<ul> <li>4-way measuring</li> <li>Accuracy +/008"</li> </ul>		L.
		Supplied with clip-on v		
Order Number A54-101-175	Description Poly-Cal Electronic Caliper	List Price \$24.60	Sale Price \$19.50	
A54-100-350	CR2032 Battery	5.50		
F thru 12	2" Economy Digital (	-		
hanit	Improved Design	Ceramic capacitive sens     Stainless steel frame	sor	(
	and the second second	<ul> <li>Direct Inch/Metric conve</li> </ul>	rsion	
244 2444	- 49	• Accuracy: .001"/.02mm .0015"/.04mm (8" & 12"	models)	
	NEW!	<ul> <li>Resolution: .0005"/.01m</li> <li>Large easy-to-read LCD</li> </ul>		
	IVE IV:	<ul> <li>Absolute referencing</li> <li>Includes molded case</li> </ul>		15
Order Number \54-100-004-2	Range 0-4"/100mm Caliper	List Price \$94.10	Sale Price \$75.60	
454-100-000-2	0-6"/150mm Caliper	109.75	80.40	17
A54-100-008-2 A54-100-112-2	0—8"/200mm Caliper 0—12"/300mm Caliper	128.80 168.00	101.20	- (
	CR2032 Battery	5.50		
Nater Res	sistant IP54 Electro Improved Design	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm	version n <i>(6" models)</i>	ľ
	sistant IP54 Electro	• Water resistant to IP54     • Stainless steel frame     • Direct Inch/Metric com	version n <i>(6" models)</i> mm	
Water Res	sistant IP54 Electro Improved Design NEW!	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001".02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price	version n (6" <i>models</i> ) mm CD display <b>Sale Price</b>	
Nater Res	sistant IP54 Electro Improved Design. NEW! Best Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     \$123.20     179.20	version n ( <i>6" models)</i> mm CD display	ł
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     S123.20	version n (6" <i>models)</i> mm 2D display <b>Sale Price</b> \$95.20	t
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     S123.20     179.20     5.50     Maximum Error: .001"//	version n(6" <i>models</i> ) mm 2D display 20 display	t
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     \$123.20     179.20     5.50      Maximum Error: .001"/     4-way measurement,'	version n(6" <i>models</i> ) mm 2D display 20 display	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case <u>List Price     \$123.20     179.20     5.50     Maximum Error: .001"/     4-way measurement, i     depth and step     Resolution: .0005"/.01 </u>	version n(6" <i>models</i> ) mm 2D display 2D disp	t
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case <u>List Price     \$123.20     179.20     5.50     Maximum Error: .001"     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0055"/.01 </u>	version n(6" <i>models</i> ) mm 2D display 2D disp	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     S123.20     179.20     5.50     Maximum Error: .001"/     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.01     Repeatability: .0005"/.01	version n(6" models) mm 2D display 2D display 255.20 141.30 7.02mm nside, outside, mm 01mm version	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design NEW: Bange 0-6"/150mm Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case <u>List Price     \$123.20     179.20     5.50     Maximum Error: .001"     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.     Range: 6"/150mm     Direct inch/metric com     Temperature range 5 t </u>	version nf(6" models) mm 2D display 2D display 2D display 2D display 2D display 2D display 200 200 200 200 200 200 200 200 200 20	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design Improved	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     S123.20     179.20     5.50     Maximum Error: .001"/     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.01     Hardened stainless sta	version n (6" models) mm CD display Sale Price \$95.20 141.30 141.30 /.02mm nside, outside, mm 01mm version 01mm version 0 40C° work- rage	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design Improved	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     \$123.20     179.20     5.50      Maximum Error: .001",     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.01     Repeatability: .0005"/.01     Reperature range 5 t     ing; -20 to 60C° in sto	version n(6" models) mm 2D display 2D display 2D display 2D display 2D display 252.20 141.30 141.30 141.30 01mm 01mm 01mm version 040C° work- rage sel construction	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design Improved	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case     List Price     S123.20     179.20     5.50     Maximum Error: .001"/     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability:	version n(6" models) mm 2D display 2D display 2D display 2D display 2D display 252.20 141.30 141.30 141.30 01mm 01mm 01mm version 040C° work- rage sel construction	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design Improved	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case <u>List Price     \$123.20     179.20     5.50     Maximum Error: .001"/     4-way measurement,     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.0     Repeatability: .0005"/.01     Repeatability: .0</u>	version nf(6" models) mm 2D display 2D display 2D display 2D display 2D display 252.20 141.30 141.30 141.30 01mm 01mm 01mm version 040C° work- rage sel construction	
Vater Res           Voter Number           A54-100-777-2           A54-100-350	sistant IP54 Electro Improved Design Improved Design I	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case <u>List Price     \$123.20     179.20     5.50     Maximum Error: .001",     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.02     Range: 6"/150mm     Direct inch/metric com     Temperature range 5 t     ing: .20 to 60C° in sto     Hardened stainless ste     RS-232 output     Features Absolute/Rel     ing Modes     Hold function </u>	version nf(6" models) mm 2D display 2D display 2D display 2D display 2D display 252.20 141.30 141.30 141.30 01mm 01mm 01mm version 040C° work- rage sel construction	
Vater Res         Vater Res	sistant IP54 Electro Improved Design Improved Design NEW! Electronic IP54 Caliper 0-12"/300mm Electronic IP54 Caliper CR2032 Battery Electronic Caliper Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Save Sa	Water resistant to IP54     Stainless steel frame     Direct Inch/Metric com     Accuracy: .001"/.02mm     Resolution: .0005"/.01     Absolute referencing     Large easy-to-read LC     4-way measurement     Includes molded case <u>List Price     \$123.20     179.20     5.50     Maximum Error: .001",     4-way measurement, i     depth and step     Resolution: .0005"/.01     Repeatability: .0005"/.01     Repeatability:</u>	version nf(6" models) mm 2D display 2D displ	

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

TOOL-A-THON

wler

XTRA-V	ALUE CAL Electronic Calipers	
K-SERIES	<ul> <li>Accuracy: .001"/.02mm (6" models)</li> <li>Stainless steel frame</li> <li>Large easy-to-read display</li> <li>Resolution: .0005"/.01mm</li> <li>Direct inch/metric conversion</li> <li>Absolute/Incremental Measurement</li> <li>Arway measuring</li> <li>Includes molded case</li> </ul>	

Order Number	Range	Display Type	List Price	Sale Price
A54-101-150-2	6"/150mm	Regular Display	\$45.00	\$31.80
A54-101-600-1	6"/150mm	Super Large Display with hold feature	56.00	37.50
A54-101-200-1	8"/200mm	Regular Display	67.20	56.50
A54-101-800-1	8"/200mm	Super Large Display with hold feature	84.00	63.50
A54-101-300-1	12"/300mm	Regular Display	90.00	88.60
A54-101-900-1	12"/300mm	Super Large Display with hold feature	110.00	83.40
A54-100-350	CR2032 Battery		5.50	

## **EURO-CAL**<sup>IV</sup> Electronic Calipers

5000		100-330-1 CAL M		FRIC • FR	ACTION
	14				A54-100-332
Protected te: IP54 COLLART & FLUE RESISTANT	, S	ave 35%	<ul> <li>Reads in inch</li> <li>Direct inch/me</li> <li>Absolute/Incre</li> <li>Water resistar</li> <li>Resolution: 0</li> <li>(<i>Fractions in 1</i>)</li> <li>Stainless stee</li> <li>4-way measure</li> <li>Includes mold</li> </ul>	, metric & frac etric/fraction c emental Meas nt to IP54 star 005"/.01mm 1/64" increme ing	conversion surement ndards onts)
Order Number	Description	nania Oslinan	Accuracy .±.001"/.02mm	List Price	Sale Price
A54-100-330-1 A54-100-331	6"/150mm Euro-Cal IV Elect 8"/200mm Euro-Cal IV Elect		±.001"/.02mm	\$111.95 132.50	\$76.30 95.60
A54-100-332 A54-100-350	12"/300mm Euro-Cal IV Elec CR2032 Battery		±.0015"/.03mm	170.00 5.50	126.30
XTRA-P		• All siz • Resol • Inch/n • Includ		es offset for in ustment screv m	
Order Number	Range	Jaw Depth	Accuracy	List Price	Sale Price
A54-100-312	0-12"/300mm Caliper	3.5"	.002"/.04m <mark>m</mark>	\$193.75	\$159.50
A54-100-024-1	0-24"/600mm Caliper	4" 4.0"	.003"/08mm	282.25	239.40

CR2032 Battery

0-40"/1000mm Caliper

Prices & Specifications are subject to change without notice.

4.9"

.004"/10mm

1170.35

5.50

649.00

## **Ultra-Cal III Heavy Duty Electronic Caliper**

Heavy Duty Ultra-Cal III, made in Germany, combines the Swiss-patented Sylvac non-contact inductive measuring system with output capabilities.



Order Number	Range	Overall Accuracy	List Price	Sale Price
Knife Jaws				
A54-100-012	<b>NEW</b> 0-12"/0-300mm	.0015"/.04mm	\$968.00	\$868.00
A54-100-020	<b>NEW</b> 0-20"/0-500mm	.002"/.05mm	\$1584.00	1200.00
Cross Jaws				
A54-100-212	<b>NEW</b> 0-12"/0-300mm	.0015"/.04mm	\$1122.00	1000.00
A54-115-333	RS232 Opto Cable		119.00	

## **EZ-ID/OD Electronic Gage**

N	<ul> <li>4" to 20"/100 to 500mm of inch/Metric/Fraction Com</li> <li>4" preset</li> <li>2ero set</li> <li>Hold function</li> <li>Preset measuring depth a</li> <li>Resolution: 0.0005"/0.011 (fractions in 1/64" increm</li> <li>Protected to IP54 specific</li> <li>Beam has vernier scale t</li> <li>Thumblock</li> <li>Direct RS232 output</li> <li>Includes wooden case</li> </ul>	at 1" or 1.5" mm tents)	Hereiter and the Hereit
Order Number	Range	List Price	Sale Price
A54-150-020 A54-100-350	<b>NEW</b> 4"-20"/100-500mm EZ-ID/OD Electronic Gage CR2032 Battery	\$360.00 5.50	\$299.00

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.


olume -

## **Heavy Duty Dial Caliper**

- Graduations: .001"
- · Large .100" one-rev dial
- Depth rod
- 4-way measurement
- · Cross-jaws for direct internal measurement
- Stainless steel, satin chrome finish
- Includes wood case

Order Number	Range	Jaw Length	List Price	Sale Price
A52-025-108	8" Caliper	2.5"	\$128.25	\$86.50
A52-025-112	12" Caliper	2.875"	186.50	129.50

## 0-6" Dial Calipers



## **Extended Range Dial Caliper**

	Graduations: .001"     Stainless steel construction     Satin chrome finish     Depth rod     .500" internal measuring nibs     Includes fitted case		SOL-A-THE EST SEL	PRESS
Order Number	Range	Depth of Jaws	List Price	Sale Price
A52-008-018	18" Caliper	3.125"	\$232.90	\$178.20
A52-008-024	24" Caliper	3.375"	282.25	221.20

Prices & Specifications are subject to change without notice.

14



## **Machinist Grade Dial Calipers**



A52-008-706

A52-008-707

A52-008-714

4-way measuring

- Solid stainless steel construction
- Silky smooth movement throughout
- .100"/2mm range per revolution
- .001"/.02mm reading dial face
- Tough shockproof gearing
- Supplied in shop-hardened case

		Dial Face	List	Sale
Order Number	Range	Color	Price	Price
A52-008-704	0-4"	White	\$51.50	\$41.20
A52-008-714	0-4"	Black	51.50	41.20
A52-008-706	0-6"	White	70.50	54.20
A52-008-707	0-6"	Black	70.50	54.20
A52-008-709	0-150mm (Metric Model)	Yellow	70.50	54.20
A52-008-708	0-8"	White	88.40	66.20
A52-008-712	0-12"	White	117.05	89.60

/olume 14.2

15

## **Snap-Cal**

Fowler's Inch, Metric & Fraction reading Snap Caliper is ideal for measuring a wide range of materials from metal, plastics and glass to small wires, fibers and paper.



L





18

Order Number A52-562-105	Departi		a shop-hardened	d case!	t Points § .120" rohase	
A32-302-103	Descrip X-Test	ption & Xtra-Mag Combo		List Price \$167.20	Sale Price \$135.80	
Six equally space Made in the USA Edge finder lights Repeatability: .00 Works on any con	instantly when st			A54-575-600 A54-575-6	525 A54-575-650	
	-			beep" at time of c		
Order Number A54-575-600	Stylus Sha .200" 1/2	2" NO	12 volt	List Price \$28.00	Sale Price \$22.85	
A54-575-625 A54-575-650	.200" 1/2 .400" 3/4		12 volt 12 volt	98.75 98.75	87.95 87.95	
X-GII Lubrica Synthetic lubricat anti-friction additi Sub-micron partic penetration and of Antistatic additive dust and dirt Contains no solve mable gases PH neutral 2.5 oz. spray bott	Int and F ulated for precision at enriched with m ves cle size allows for lurability prevents the attra ents, propellants o	ultiple maximum action of	nt	The	a Utimati vicant for Precision	+1 aunton
					Tooli	

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

19

N

X-Test Indicator—TWICE the range of most indicators!



Order Number	Description	Graduations	Dial Diameter	Dial Reading	List Price	Sale Price
A52-562-001	X-Test Indicator	.0005"	1-1/2"	0—15 <mark>—0</mark>	\$117.55	\$109.95
A52-562-002	X-Test Indicator	.0005"	1"	0—15 <mark>—0</mark>	117.55	109.95
A52-562-003	X-Test Indicator	.001"	1"	0—15 <mark>—0</mark>	117.55	109.95
A52-562-007	X-Test Indicator	.01mm	25mm	0-40 <mark>-0</mark>	117.75	109.95
A52-562-008	X-Test Indicator	.01mm	38mm	0-40-0	117.75	109.95

## Vertical X-Test Indicator TWICE the range of most indicators!

- Range: .060"
- · Dial reading: 0-15-0
- Jeweled movement
- Revolution counter
- · Easy-to-read tilted dial
- Automatic reversal
- 210° Swivel arc

à.

- 5/32" stem
- Tungsten carbide point: .080"

Order Number	Description	Graduations	Dial Diameter	List Price	Sale Price
A52-562-004	Vertical X-Test Indicator	.0005"	1-1/2"	\$128.75	\$109.95
A52-562-005	Vertical X-Test Indicator	.0005"	1"	128.75	109.95
A52-562-006	Vertical X-Test Indicator	.001"	1"	128.75	109.95

## X-Test Indicator and Accessory Combo Kit

040" \$ 120



# XTEST

#### Each Combo Kit Includes:

X-Test Dial Test Indicator (see above)

TEST

- Axial support
- Height gage bar with clamp
- Adaptor sleeve: 5/32" to 3/8"
- Contact point case
- Contact point wrench
- · Complete in "Shop Hardened" case.

Order Number	Description	Graduations	List Price	Sale Price
A52-562-100	52-562-001 w/accessories	.0005"	\$172.65	\$155.40
A52-562-110	52-562-002 w/accessories	.0005"	172.65	155.40
A52-562-120	52-562-003 w/accessories	.001"	172.65	155.40

20

## **Test Indicators**

All Fowler Test Indicators include bi-directional constant clockwise rotation, automatic reversal, three dovetail mountings, jeweled movement, two dovetail clamps and a molded case.



Order	Face	Total	Dial		Dial	Point	List	Sale
Number	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
A52-562-774	white	.030"	0-15-0	.001"	1"	1/2"	\$105.30	\$62.80
A52-562-778	black	.030"	0-15-0	.0005"	1"	1/2"	111.95	62.80
A52-562-775	white	.030"	0-15-0	.0005"	1"	1/2"	111.95	62.80
A52-562-776	white	.030"	0-15-0	.0005"	1-1/2"	1/2"	117.05	68.80
A52-562-780	black	.030"	0-15-0	.0005"	1-1/2"	1/2"	117.05	68.80



Order Number	Face Color	Total Range	Dial Reading	Graduation	Dial Diameter	Point Length	List Price	Sale Price
A52-563-770	white	.008"	0-4-0	.0001"	1"	1/2"	\$111.95	\$90.40
A52-563-771	black	.008"	0-4-0	.0001"	1"	1/2"	111.95	90.40
A52-563-777	white	.008"	0-4-0	.0001"	1-1/2"	1/2"	111.95	90.40
A52-563-772	black	.008"	0-4-0	.0001"	1-1/2"	1/2"	115.30	90.40



Order	Face	Total	Dial		Dial	Point	List	Sale
Number	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
A52-562-781	white	.020"	0-10-0	.0005"	1"	1-7/16"	\$115.30	\$87.20
A52-562-782	black	.020"	0-10-0	.0005"	1"	1-7/16"	115.30	87.20
A52-562-783	white	.020"	0-10-0	.0005"	1-1/2"	1-7/16"	115.30	87.20
A52-562-784	black	.020"	0-10-0	.0005"	1-1/2"	1-7/16"	115.30	87.20

A52-562-784





Order	Face	Total	Dial		Dial	Point	List	Sale
Number	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
A52-563-677	white	.080"	0-40-0	.01mm	1-1/4"	1/2"	\$64.90	\$51.90
A52-560-060	white/red	.020"/.05mm	0-10-0/025-0	.0005"/.01mm	1-1/2"	1/2"	88.40	66.30

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

21

Volume 14.2

## **High Precision Dial Gage Stand**

Fowler's High Precision Dial Gage Stand is 14" in overall height and is supplied with 2 anvils: flat and serrated.

- Quick positioning and adjustment
- Zero settings with knob for fine adjustment
- Fine adjustment of 5/32"
- Total height of column 14"
- Can hold indicators with stems of 3/8"
- Diameter of column .980"
- Supplied with two 2-3/8" diameter anvils, flat and serrated



# INDI-XIIIC Electronic Indicators

NEW!

Now available in .5"/12.5mm & 1"/25mm ranges!

#### INCH • METRIC • FRACTION

- Direct Inch/Metric Conversion
   Auto Off feature
  - 2-1/4" dial face
  - · Lugback and 3/8" stem mountings
  - Resolution .0005"/.01mm
  - Tolerance indicators
  - · Absolute/incremental reading

WLER HIGH PRE

- Floating zero
- · Carbide tipped point

Low Cost, High Quality, Multi-Function Indicators

### **Carbide-tipped point!**


Order Number	Description	List Price	Sale Price
A54-520-250	1"/25mm Indi-X Blue Electronic Indicator	\$94.00	\$58.50
A54-520-260	1"/25mm/64ths Indi-X Blue Inch-Metric-Fraction Electronic Indicator	96.25	61.50
A54-520-255	.5"/12.5mm Indi-X Blue Electronic Indicator	87.30	51.50





NEW!

A52-585-085 (Indicator not included)



A52-565-038 (Indicator not included)



#### Features:

MACHINIST GRADE! For MAXIMUM Precision

- All accept 3/8" indicators
- Mag base and HOLD-TEC with fine adjust also accepts 8mm indicators
- All have dovetail clamps for test indicators
- Mag base features 2 fine adjusts making it 6-Axis Mag Base

A52-565-036 (Indicator not included)

- HOLD-TEC can be mounted in drill chucks, collets, dial gage stands with 8mm mount diameter to make a quick transfer stand
- Mag base has 180 lb. pull
- Adjust to any position
- Powerful On/Off mag base
- Central locking system

Order Number	Description	List Price	Sale Price
A52-585-085	NEW HOLD-Tec Mag Base with Double Fine Adjust	\$147.30	\$125.00
A52-565-036	NEW HOLD-Tec without Fine Adjust	82.70	75.00
A52-565-038	NEW HOLD-Tec with Fine Adjust	89.90	80.00

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

23

Volume 14.2



- Auto Off feature
- · 2-1/4" dial face
- · 3/8" stem 4-48 thread
- Resolution .00005"/.001mm
- · Accuracy: .00016"/.004mm (to 1")
- Tolerance indicators
- · Absolute/incremental reading
- Lugback supplied on 1/2" model.
   Lugbacks for 1" and 2" models, 52-525-605
- · Floating zero
- · Carbide tipped point



Protected to:

RESISTANT

Description

CR2032 Battery

Absolute data cable

**Carbide-tipped points!** 

0-1"



List Price

\$329.00

369.00

479.00

139.00

5.50

0-2"

Sale Price

\$279.30

319.20

429.60

-owler

ZERO/ABS

Order Number
A54-520-305
A54-520-310
A54-520-320
A54-100-350
A54-520-399

24

Prices & Specifications are subject to change without notice.

.5"/12.5mm Indi-Max Electronic Indicator with point set

1"/25mm Indi-Max Electronic Indicator with point set

2"/50mm Indi-Max Electronic Indicator with point set

## UltraTast Test Indicators

## Horizontal Test Indicators

- · Box-type housing opens on one side only.
- · Bottom and side walls are one piece construction which encloses and protects the movement from shocks and damage.
- Self-contained movement

O A5 A5 A5 A5

- · Jeweled movement bearings, precision gears and pinions for maximum sensitivity and accuracy
- · Satin-chrome finish is corrosion proof
- Stylus: ball diameter .080"/2mm
- Swivel range 220° on all models
- Includes 1/4" & 5/16" Dovetail clamps

		Measiuring	Dial	Stylus	Measuring
rder No.	Reading	Range	Diameter	Length	Force
52-568-005	.0005"	±.015"	1.083"	.453"	0.15N
52-568-010	.0005"	±.015"	1.50"	.453"	0.15N
52-568-015	.0001"	±.004"	1.50"	.453"	0.15N
52-568-022	.0005"	±.015"	1.083"	1.417"	0.07N
52-568-022	.0005"	±.015"	1.083"	1.417"	0.07

Order Number	Description	List Price	Sale Price
A52-568-005	NEW UltraTast Horizontal Test Indicator	\$121.00	\$80.00
A52-568-010	NEW UltraTast Horizontal Test Indicator	137.50	90.00
A52-568-015	NEW UltraTast Horizontal Test Indicator	176.00	120.00
A52-568-022	NEW UltraTast Horizontal Test Indicator	196.90	130.00

NEW!

## **Height Transfer and Squareness Gage**

## **A PERFECT** match for UltraTast Indicators!

Description

- · Used for a variety of surface plate applications
- · Large fine adjustment knob for precise control
- · Swivel clamp anchors swivel and indicator for added accuracy
- · Rear surface of the gage has a reference surface to square against a master for checking squareness
- Includes a 7.5" post, indicator rod and clamp

Order Number

A53-620-010

Indicator and standard shown not included

100 C
10 March 10
and the second sec
States of States
Contraction of the local division of the loc
me
_
-
the second se
and the second second
and the later of t
and the second

List Price Sale Price \$199.00 Height Transfer and Squareness Gage \$286.00 25

GERMANY GERMANY

40.00 or

re on all lodels!

< 

Fowler

12-568-005

Ultratest

0005

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

## CHROME FLEX MAG SET

#### With MIL Electronic Indicator or AGD Black face Indicator

OOL-A-THON

#### Indi-X Blue Indicator features:

- **Direct Inch/Metric Conversion**
- 1"/25mm travel Auto Off feature
- 2-1/4" dial face
- Lugback and 3/8" stem mountings Resolution .0005"/.01mm
- **Tolerance indicators**
- Absolute/incremental reading Floating zero
- Carbide tipped point

#### Flex Arm Mag Base features:

- Corrosion resistant chrome plated flex arm
- · 85 lb. pull magnet
- Holds rigidly in almost any position
- V-base for mounting on rounded surfaces

#### Magnetic Indicator Back features:

- Use for positioning indicator on most
- metal surfaces
- Protective coating

#### All in a shop-hardened case.

Included Magnetic Indicator Back for mounting to most metal surfaces!

BEST SELLER!

SERIES



#### AGD Indicator features:

- AGD Group 2
- Dial diameter: 2-1/4"
- Travel: 1"
- · Reading: .001"
- Continuous reading: .100"
- Carbide tipped point

#### See the Indi-X Blue on page 22!

Order Number	Description	List Price	Sale Price	
A54-585-100	Chrome Flex Mag and Indi-X Blue Electronic Indicator Set	\$230.95	\$125.00	
A52-585-500	Chrome Flex Mag and AGD Black Face Indicator Set	173.25	123.00	

## **Fine Adjust Mag Base Set**

#### With INDEX COLOR Electronic Indicator or AGD White face Indicator

#### Indi-X Blue Indicator features: **Direct Inch/Metric Conversion** Included Magnetic 1"/25mm travel Indicator Back for Auto Off feature mounting to most 2-1/4" dial face metal surfaces! Lugback and 3/8" stem mountings Resolution .0005"/.01mm **Tolerance** indicators Absolute/incremental reading Floating zero Carbide tipped point Magnetic Base features: 85 lb. pull Fine adjustment. V-bottom base

#### AGD Indicator features:

- AGD Group 2
- Dial diameter: 2-1/4"
- Travel: 1"
- Reading: .001"
- Continuous reading: .100"
- Carbide tipped point

#### See the Indi-X Blue on page 22!

Order Number	Description	List Price	Sale Price
A54-585-075	Fine Adjust Mag Base Set with Indi-X Blue Electronic Indicator Set	\$196.35	\$145.00
A52-585-125	Fine Adjust Mag Base with AGD White Face Indicator Set	\$150.15	70.00



Prices & Specifications are subject to change without notice.

26

#### Magnetic Indicator Back features:

Use for positioning the indicator on most metal surfaces.

Protective coating

All in a shop-hardened case.



## **XTRA-SURF** Surface gage with a built-in Switchable Magnetic Base



All in a Shop-Hardened Case!



- Set includes 3-1/8" x 2-1/16" permanent magnetic base with on/off switch, fine adjustment on base and a 5/16" x 9" upright
- .0005" test indicator No. A52-562-778 (see page 21 )
   with .040", .080" & .120" contact points
- Swivel clamp to mount indicator
- Two dovetail stems: 5/32" & 3/8"
- A 4" hardened scriber
- Form fitted shop-hardened case for easy accessibility and storage

Order Number	Description	List Price	Sale Price
A52-155-747	Xtra-Surf	\$213.40	\$122.50
A52-155-743	Xtra-Surf without indicator	105.85	91.50

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

27

Volume 14.2



TOOL-A-THON

28



Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

29

# Sylvac Closeout Sale!

**Ultra-Digit Mark IV & V Electronic Indicators** 

00000

00

ā

nnnn

00

00000







# ONCE THEY'RE **GONE** THEY'RE GONE!

#### Features:

**TOOL-A-THON** 

- Inductive measuring system
- Inch/mm conversion
- Floating zero
- Preset functions
- Direct RS232 output
- Resolution .00005"/.001mm (except for A54-520-905)
- Display rotates 270°

Order Number	Description	List Price	Sale Price
A54-520-790	Mark IV 0500"/12.5mm	\$559.00	\$475.00
A54-520-791	Mark IV 0500"/12.5mm w/8mmØ stem, M2.5 thr	ead 575.00	450.00
A54-520-792	Mark IV 0-2"/50mm	1141.00	900.00
A54-520-794	Mark IV 0-4"/100mm	1305.00	1100.00
A54-520-796	Mark IV 0-6"/.00005"	1747.00	900.00
A54-520-876	Mark V 0500"/12.5mm w/8mmØ stem, M2.5 three	ead 648.00	525.00
A54-520-900	Mark V for cylinder bore gages only, 1/2" trav	el 648.00	525.00
A54-520-905	Mark IV 0-6"/.0005"	1978.00	1200.00



## **Economy Depth Micrometers**




- Satin chrome finish
  - · Base surface hardened, ground & lapped
  - Ratchet thimble

  - Locking clamp
    .001" Graduation
  - · Rod diameter: .176"
  - · Includes shop-hardened case.

Order Number	Range	Graduation	Base	List Price	Sale Price
A52-225-110	0-4"	.001"	2.5"	\$112.60	\$99.80
A52-225-112	0-6"	.001"	2.5"	136.80	122.60
A52-225-114	0-4"	.001"	4"	119.30	107.00
A52-225-116	0-6"	.001"	4"	142.50	136.50

## **Economy Digit Counter Depth Micrometer**



- Microfine .001" graduations
- · 4" base constructed of tool steel, hardened and ground
- Satin chrome finish
- Ratchet thimble
- · Locking clamp
- · Rod diameter: .176"
- Includes wrench and fitted case

Order Number	Range	Graduation	Base	List Price	Sale Price
A52-225-176	0-6"	.001"	2.5"	\$141.05	\$132.00
A52-225-226	0-6"	.001"	4"	152.90	140.00

## **IP54 Electronic Depth Micrometers**



Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

31

Volume 14.2



Prices & Specifications are subject to change without notice.

32

finish permit easy Accuracy: ±.0002 Ratchet stop thim Easy zero adjustr Meets or exceeds Includes a setting	2" (.005mm) ble ment on the sleeve s Federal accuracy specs ring		Includes s	setting ring!
Order Number	er wrench and a fitted cas Description Inside Micrometer	e Range	List Price	Sale Price \$121.50

- · Set includes G clamp, tool post base, vertical rod, swinging arm, ball anvil, 1/2" anvil, thumb clamp and 11/32" standard anvil.
- Back plunger indicator is fully jeweled

Dial Dia.	Graduations	Dial Reading	Range	List Price	Sale Price
1-1/2"	.001"	0-100	.100"	\$143.00	\$120.00
1-1/2"	.001"	0-100	.100"	68.20	56.00
	1-1/2"	1-1/2" .001"	1-1/2" .001" 0-100	1-1/2" .001" 0-100 .100"	1-1/2" .001" 0-100 .1 <mark>00" \$143.00</mark>

## **Ultra-Cal III Electronic Groove & Recess Gage**



- Direct RS-232 output
- · External measurement 0-12" depending on accessories

100-000

- Internal measurement 1-13/16"-13-1/2" depending on accessories
- Resolution: .0005"(.01mm)
- Accuracy: ±.0015"(.04mm)
- Sylvac capacitive measuring system

- Measures rotors and brake drums
- Two preset memories
- Inch/metric conversion
- · Interchangeable anvils for inside/outside measurement
- · Includes flat and point style contacts & battery
- Uses 4-48 thread contact points
- · 4.5" Jaw length

- )		and the second sec	
Order Number	Description	List Price	Sale Price
A54-150-012	NEW 0-12" Ultra-Cal III Electronic Groove & Recess Gage	\$1149.50	\$650.00
A54-115-333	RS-232 Cable	119.00	

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

33

Volume 14.



JOL-A-THON

## **Bore Gage Setting Master Kit - Inch & Metric**

Fowler's Bore Gage Setting Master Kit is used for accurately setting any bore gage up to 6"/150mm in diameter to an accuracy of .0001"/.003mm.

#### **Each Set includes:** Setting Device • Base anvil: 2.750" x .80" Includes: Adjustable anvil 2.375" x .375" (two each) Internal capacity: 6"/150mm Bore gage setting master and gage block set. · Depth capacity: 1"/25mm All in a custom-fitted Centralizer capacity width: 2.625"/66.7mm aluminum case! Quick-release holder for fast adjustment Can also be used for external setting, depending on application (external mics, snap gages, caliper qaqes) Economy Gage Block Sets Inch model: · 36 piece Tolerances to .00005" Certificate of Calibration to N.I.S.T. Metric model: 33 piece AS-2 grade Certificate of Calibration to N.I.S.T. Order Number Description List Price Sale Price

A53-646-010	Metric Bore Gage Set	tting Master Ki	t	\$295.00	\$259.80
Caliper.	Micrometer	& Sna	p Gage	Checking	Set

Inch Bore Gage Setting Master Kit

Fowler's setting master is quick, easy and extremely accurate. It comes with a certificate of calibration and a fitted aluminum case. Save time and money by calibrating your own measuring tools quickly and easily.



A53-646-000

- Calibration certification traceable to N.I.S.T. standards
- Stand height: 12.5"
- 9 pc. Grade AS-0 gage block set (sizes: .625", .100", .125", .200", .250", .300", .500", 1.000" & 2.000"
- Certificate of calibration is traceable to N.I.S.T. standards & provides the individual deviation of each block
- Optical flat (flatness: .000004"; Parallelism: .00002")
- 4.0mm ball end T-handle hex wrench

NEW!

Worn blocks can be easily replaced!

\$275.00

\$198.95

and the second se		and a second	and the second sec
Order Number	Description	List Price	Sale Price
A53-813-001-1	Complete Caliper, Micrometer and Snap Gage Checking Set	\$303.21	\$272.37
A53-813-002-0	NEW Mic Checker without Blocks	145.00	\$119.00

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

/olume

## **Quick Check Multi-Function Check Standard**

· One compact, multi-function, precise standard

NEW!

- · Can be used to check and verify a multitude of measuring instruments
- · Checks calipers, micrometers, depth gages, bore gages, test and dial indicators, caliper gages, height gages, protractors, combination sets and more
- Supplied with a manufacturer's test certificate and fitted wood case
- All sizes marked are actual

Order Number	Description	List Price	Sale Price
A53-813-015	NEW Quick Check Multi-Function Check Standard	\$1490.00	\$1375.00

NEW!


## Large Square Gage Blocks

Grade Ø

h

- NIST Traceable
- · Vertically more stable then rectangular blocks
- · Large sizes help eliminate block stacks
- Meets or exceeds Federal Specifications ASME B89.1.9-2002

Order Number	Description	List Pr
A53-676-216	NEW 5" Large Square Gage Block	\$209
A53-676-218	NEW 6" Large Square Gage Block	251
A53-676-220	NEW 7" Large Square Gage Block	288
A53-676-222	NEW 8" Large Square Gage Block	340
A53-676-224	NEW 10" Large Square Gage Block	473
A53-676-226	NEW 12" Large Square Gage Block	526
A53-676-228	NEW 16" Large Square Gage Block	790
A53-676-230	NEW 20" Large Square Gage Block	921



List Price

\$209.00 251.00

288.00

340.00

473.00 526.00

790.00

921.00

Sale Price \$190.00

235.00

273.00 320.00

450.00

500.00

750.00

870.00

# Fowler TOOL-A-THON

# **XTRA-VALUE** 9" Electronic Level

Fowler's 9" Laser Level provides instant 4 x 90° digital inclination display. With embedded magnets on its measuring surface, a beamsplitter projects a 90° laser cross hair for leveling at-a-distance. It also includes a 1/4-20 mount for tripod use.

- Measuring range: 4 x 90°
- Resolution: .05°
- Accuracy: ±.2<sup>c</sup>
- Repeatability: ±.05
- Standard 9 volt battery (250 hours life)
- Dimensions: 9"L x 1"W x 2-1/4"H
- · Includes two-way level and plumb vials
- Reversible reading for inverted use



List Price

\$67.15

Sale Price

\$55.99

Order Number A54-440-600 Description Xtra-Value 9" Electronic Level

# mini-MAG Protractor



The mini-MAG Protractor provides instant 360° digital inclination display of any angle with the additional unique feature of embedded magnets on both sides and the bottom which make it ideal for a variety of measurements.

A-THOA

VLER HIGH

- Embedded magnets with 3.5lb. pull
- Uses standard 9V battery (250 hrs.)
- Measuring range: 360° (4 x 90°)
- Display automatically inverts
- Resolution: .05°
- Accuracy: ±.2°
- Repeatability: .05
- Hold feature



Display inverts for easy reading!

Dimensions: L: 2.375" x W: 1.375" x H: 2.375"

Order Number	Description	List Price	Sale Price
A54-422-450-1	Mini-Mag Protractor	\$89.55	\$69.50

# Fowler Digi-Pro Electronic Protractor

The Digi-Pro electronic protractor includes embedded magnets for unique measurement areas. On/Off, Zero, Hold and Reverse feature to invert the display for easier reading in certain situations.

- Embedded 25 lb. pull magnets
- Full, 360° measuring range
- Accuracy: ±.2°
- Repeatability: ±.05°
- Resolution: .05°
- · Invertible display feature
- Voltage: Standard 3V lithium battery





# USE THE DIGI-PRO TO MAKE FAST AND ACCURATE ANGULAR MEASUREMENTS!

Order Number	Description	List Price	Sale Price
A54-440-740-1	4" Digi-Pro Electronic Protractor	\$82.50	\$62.80
A54-440-775-1	12" Digi-Pro Electronic Protractor	98.95	67.80
A54-100-350	CR2032 Battery	5.50	

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

Volume '

# 12" Telescoping Gage

Another great tool for easy and accurate measurements. Under spring tension, the plungers of the gage expand from the center to the size of the hole being measured and are then locked in place using the knurled knob. Final hole size is obtained by measuring over the contacts with a micrometer or vernier caliper.

# 12" Reach!

- Contact points are constructed of hardened tool steel, precision ground.
- Double action rigid handle with self-centering feature for quick checking of inside measurements
- Constant spring tension for uniform feel
- Covers a measuring range of 5/16" to 6" with measurable depths of 12"

NEW!

Includes fitted vinyl case

Order Number A52-470-007

Description NEW 12" Telescoping Gage Set

### List Price Sale Price \$119.00 \$78.50

### 2 Dimensional Coaxial Indicator Sets DA

Use the 2D Coaxial Set for accurate component centering and positioning in most machining applications. The 2D Coaxial indicator can be used at any angle and the dial remains stationary during the rotation of the machine spindle.

WLER HIGH P

GREAT SHOP TOOL!

### Features:

- Indicator assembly with 1.6" (42.5mm) diameter dial
- · Graduations and revolution counter .0005" (.01mm)
- · 3 Internal and 3 External feelers
- Center point feeler
- Restraining arm
- Complete in a fitted case



38

### Specifications:

- Length: 6-7/8" (175mm)
- Shank: 3/8" dia. x 7/8" (10mm x 20mm) long Feeler ball: 1/8" (3mm) dia.
- Dial readings: 0-50
- · Measuring range: .250" (6mm) axis offset
- Speed—recommended not to exceed approx. 800 RPM
- Locating accuracy to within .0002" (.005mm) of true center
- Capacity depends on feelers installed, but overall range is 5/32-12" (4-300mm) internal diameter; 0-12" (0-300mm) external diameter

Order Number	Description	List Price	Sale Price
A52-710-025	2D Coaxial Set-Inch	\$223.10	\$166.80
A52-710-030	2D Coaxial Set-Metric	223.10	166.80

## **Thickness Gages**

- · Each leaf of the thickness gage made of fine tempered steel, harened
- The exact thickness is marked on each leaf
- Steel case with lock nut
- Meets U.S. Federal Specifications



Order Numbe	r Description	List Price	Sale Price
A52-485-006	NEW Tapered Thickness Gages-Inch.26 Leaf Set: .0015", .002", .0025", .003",	\$14.00	\$11.99
	.004", .005", .006", .007", .008", .009", .010", .011", .012", .013", .014",		
	.015", .016", .017", .018", .019", .020", .021", .022", .023", .024" and .025".		
A52-495-010	Length: 3". NEW Tapered Thickness Gages-Metric. 20 Leaf Set: 0.05mm, 0.10mm,	\$17.60	\$9.99
A32-403-010	0.15mm, 0.20mm, 0.25mm, 0.30mm, 0.35mm, 0.40mm, 0.45mm,	φ17.00	<i>\$3.33</i>
	0.50mm, 0.55mm, 0.60mm, 0.65mm, 0.70mm, 0.75mm, 0.80mm,		
	0.85mm, 0.90mm, 0.95mm and 1mm. Length: 100mm.		

### **Screw Pitch Gages**



Acme Screw Pitch Gage A52-485-030 · Narrow designed blades permit use for internal and external screw threads

- · Locking device at each end to secure all blades for storage or position
- · Correct pitch is determined by matching blade teeth with threads · Precisely ground and finished
- · Blades marked with thread size


Screw Pitch Gages

### Acme Screw Pitch Gage (29° angle)

· Made of fine stainless steel. Each blade is 3-1/2"/90mm long and

.03"7.8mm thick			
Order Number	Description	List Price	Sale Price
Inch Series A52-485-015 Metric Series	NEW Screw Pitch Gage with 30 blades: 4 to 42 pitch standard V three	ıd \$10.45	\$7.99
A52-485-020 Acme Series	NEW Screw Pitch Gage with 24 blades: 0.25mm to 6.0mm	10.45	7.99
A52-485-030	NEW Acme Screw Pitch Gage with 16 blades (1, 1-1/3", 1-1/2", 1-3/4" 2-1/2", 3, 3-1/2", 4, 5, 6, 7, 8, 9, 10 &12 pitch)	, 2, 91.30	85.00

# **Thread Measuring Wire Set**



Volume 14.2

### Rules

- EZ-Read Black Face Rules
- Hardened stainless steel
- White easy-to-read microfine graduations against a black, non-glare finish

### Satin Chrome Rules

- Tempered steel
- Non-glare
- Sharp, easy-to-read microfine graduations

### **Golden Rules**

- Titanium coated for superior wear resistance
- Non-glare finish=RC80
- Scratch resistant microfine graduations with excellent clarity and contrast

### GRADUATIONS 4R: 8ths, 16ths, 32nds, 64ths

.....

**5R:** 32nds, 64ths, 10ths, 100ths

stammer to semanter seman

### **RIGID STEEL RULES**

Order Number	Finish	Size	Reading	List Price	Sale Price
A52-330-006	Satin Chrome	6"	4R	\$9.90	\$8.60
A52-337-006	Black	6"	4R	8.35	6.25
A52-339-006	Golden	6"	4R	20.60	17.25
A52-330-012	Satin Chrome	12"	4R	17.20	14.60
A52-337-012	Black	12"	4R	17.20	10.70
A52-339-012	Golden	12"	4R	39.55	33.80
A52-340-006	Satin Chrome	6"	5R	9.50	7.55
A52-347-006	Black	6"	5R	8.35	6.25
A52-349-006	Golden	6"	5R	20.60	17.25
A52-340-012	Satin Chrome	12"	5R	15.60	14.60
A52-347-012	Black	12"	5R	17.20	10.95
A52-349-012	Golden	12"	5R	39.55	33.80

### **FLEXIBLE STEEL RULES**

Order Number	Finish	Size	Reading		List Price	Sale Price
A52-295-006	Satin Chrome	6"	4R		\$9.50	\$7.05
A52-297-006	Black	6"	4R		7.80	5.75
A52-299-006	Golden	6"	4R		20.30	17.70
A52-295-012	Satin Chrome	12"	4R		14.60	13.00
A52-297-012	Black	12"	4R		12.00	9.90
A52-299-012	Golden	12"	4R		36.40	31.20
A52-300-006	Satin Chrome	6"	5R		9.50	7.05
A52-307-006	Black	6"	5R		7.80	5.75
A52-309-006	Golden	6"	5R		20.30	17.70
A52-300-012	Satin Chrome	12"	5R		14.60	13.00
A52-307-012	Black	12"	5R		12.00	9.90
A52-309-012	Golden	12"	5R		36.40	31.20

### 6"/150mm Pocket Steel Rule



Order Number	Description	List Price	Sale Price
A52-380-100	6"/150mm Pocket Steel Rule	\$6.25	\$4.95

40



K-BLOX V-Block Set

Be sure to use the	"A" prefix when ordering	Tool-A-Thon specials
	in pronk milon ordoning	roor ri mon opoolaio.

36 piece Grade Ø Rectangular Gage Block Set

81 piece Grade Ø Rectangular Gage Block Set

A53-670-038

A53-670-080

\$231.00

510.00 41

\$434.55

799.70

# 1/2" Parallel Set

- · Set of four pairs of parallels are hardened and ground
- A must for every shop
- Sizes: 1", 1-1/4", 1-1/2" and 1-3/4" in height x 6" long with 5/16" holes
- 1-1/2" and 1-3/4" parallels are 1/2" thick
- 1" and 1-1/4" parallels are 3/16" thick
- · Width & height variations: maximum .0004"
- Includes fitted case

 Order Number
 Description
 List Price
 Sale Price

 A52-437-001
 Set of four pairs of parallels
 \$203.85
 \$122.00

## 1/32" Premium Parallel Set



- ground t parallel • 10 pairs • 1/2", 5/8 • Height s • each pa
- Set
   Set

   Made from high-grade alloy steel, hardened and ground from 1/32" stock with 2 holes in each
  - 10 pairs, 6" length, 1/32" width
  - 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2" & 1-5/8"
  - Height specifications relate to consistency within each pair. Absolute heights are nominal
  - Parallelism: ±.0001"
  - · Paired in height: ±.0001"
  - Hardness: 50 HRC

Order Number	Description	List Price	Sale Price
A52-437-031	1/32" Parallel Set	\$ <mark>215.00</mark>	\$185.00

# 1/8" Premium Parallel Set

- Made from high-grade alloy steel, hardened and ground from 1/8" stock with 2 holes in each parallel
- 10 pairs, 6" length, 1/8" width
- 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2" & 1-5/8"
- · Height specifications relate to consistency within each pair
- Absolute heights are nominal
- Parallelism: ±.0002"
- Paired in height: ±.00015"
- · Hardness 58-63 HRC



Order Number	Description	List Price	Sale Price
A52-437-125	1/8" Parallel Set	\$2 <mark>63.20</mark>	\$242.00

# 1/4" Premium Parallel Set



- Made from high-grade alloy steel, hardened and ground from 1/4" stock with 2 holes in each parallel
- 9 pairs, 6" length, 1/4" width
- 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2", 1-5/8" & 1-3/4"
- · Height specifications relate to consistency within each pair
- · Absolute heights are nominal.
- Parallelism: ±.0002"
- · Paired in height: ±.0002"
- Hardness 52-58 HRC

Order Number	Description	List Price	Sale Price
A52-437-250	1/4" Parallel Set	\$32 <mark>8.90</mark>	\$275.00



# X-TRA RANGE<sup>20</sup> 20x Extended Range Microscope

Fowler's new Extended Range Microscope is ideal for viewing the surface of items that will not fit conventional microscope plates.



- 10X eyepieces with adjustable centers and rubber eyecups
- 2X objective lense
- Top swiveling light source 12 volt lamp, 110V supply
- · Positive rack and pinion focusing
- Articulated 12" long extension arm
- Heavy base plate insures stability and houses transformer which measures 5" x 8" x 2.5"
- Overall base and column height of 12"

Order Numb		cription			L	ist Price	Sale Price
A53-640-280	20X	Microscope v	vith Universal St	and		\$347.15	\$275.00
A53-640-281	-1 Rep	lacement bulk	)			11.20	
Direct Inch/ Accuracy: 0-12" 0-13" 0-24" Resolution Large, high display Hold featur ABS/INC M Floating zer Positive loc Includes mo Carbide scr	Metric Convers model: ±.0015" model: ± .002" model: ± .003" .0005" (.01 mm contrast LCD e easurement ro k bolded case iber	sion	•	24" Tw Dial Hi • Separate d register bo downward • Zero setting obtained th gage's ram, • Coarse rea .100" gradi readings ta indicator au • Dual chrom beams • Carbide-tip • Base is hau ground & la maximum f	eight ( igit counter th upward & g can be roughout th ge dings in Jations: fine iken on re .001" he plated ped scriber dened, apped for	Gage s he	
Order No.	Range	List Price \$465.90	Sale Price				
			\$331.20				
54-175-012							
54-175-012 54-175-018	0-12"/0-300mm 0-18"/0-450mm 0-24"/0-600mm	543.20 611.50	391.20 465.80	Order No.	Range	List Price	Sale Price

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

olume 1

### **Swiss Pattern File Sets**

Swiss Pattern Files are economically priced and each set includes a fitted case and 12 of the finest quality files in the most popular shapes.

Fowler Swiss Pattern Files are fine precision cutting tools used by tool and die makers, model makers, delicate instrument and part finishers for a variety of filing jobs. Made to closer tolerances than American pattern files, they are primarily finishing tools for removing burrs, trueing narrow grooves, notches, keyways, cleaning corners, smoothing small parts and similar jobs.

Order Number	Description	Length	Cut No.	List Price	Sale Price
A55-130-060	12 pc. Swiss Pattern File Set	6"	#0	\$18.65	\$9.00
A55-130-062	12 pc. Swiss Pattern File Set	6"	#2	18.65	9.00

Save

# **Super Heavy Duty Automatic Center Punch**

· Handle constructed in steel. Four knurled bands provide a sturdy grip

- · Moveable components are made from tool steel and hardened
- · The point is easily removed for sharpening
- The pressure of marking is controlled by rotating the knurled cap. Screw the cap down for heavy indentations and screw the cap upward for lighter markings.

Order Number	Description		List Price	Sale Price
A52-500-290	Super Heavy Duty Automatic Ce	nter Punch	\$19.80	\$14.00
	rked and diam- v undersized for			ST SELLER!
Order Number	Description	Range	List Price	Sale Price
A52-482-028	28 Piece Transfer Punch Set NEW 33 Piece Transfer Punch Set	3/32"-1/2" <b>1/2"-1"</b>	\$48.95 85.00	\$34.9
A52-482-030	NEW 33 Piece Transfer Punch Set	1/2 -1	85.00	72.99
Screwdr		EW!		
	minia • Featu • Scree	precision Screwdri ature work ures knurled and cl wdriver and Tool S pered point scrato	nromed swiveling et contains <b>9 scr</b>	handles <b>ewdrivers</b> ,

 Screwdriver size range: #00, #0, #1, 1/32", 3/64" 1/16", 5/64", 3/32" and 1/8"

Order Number	Description	List Price	Sale Price
A52-490-003	NEW Screwdriver Set	\$24.20	\$20.99



Wer TOOL-A-THON



# **Metal Etching Pen**

A "must" for any tool room and machine shop for general marking purposes, Fowler's metal etching pen is used on copper, copper alloy, stainless steel, hardened steel tools and castings, etc.



Use it to initial personal tools. Its low-cost, disposable design offers limitless applications.

ETCHING WARKER FOWIER Tint

Personalize your tools!

Order Number	Description	List Price	Sale Price
A52-730-005	NEW Disposable Felt Tip Metal Etching Pen, overall length is 6-1/4"	\$17.35	\$14.85

# **Steel Scribers**

	inum knurled steel tubing bod k holds hardened tempered s	y criber point, which is removable a	nd replaceable	
Order Number	Description	Overall Length	List Price	Sale Price
A52-515-005	Pocket Scriber	5.625"	\$4.70	\$2.60

- · Fine quality steel blade with fully hardened points
- · Chrome finished with knurled handle

· Hook point on opposite end

Order Number	Description	Overall Length	List Price	Sale Price
A52-515-025	Point Scriber	8.5"	\$4.70	\$2.60

# **Carbide Tipped Scriber Values!**

			Fowl	en	
Ici-	· Lightweight · Retractable	carbide tip • Knurled	grip · Machine	d aluminum body	Pocket clip
Order Number	Description	Overall	Length	List Price	Sale Price
A52-500-050	Carbide Super So	riber	6.5"	\$29.90	\$26.80
A52-500-055	Carbide Refill			9.50	
				-	-
-	Lightweight      Retractable			ed aluminum body	
Order Number		Overall L		List Price	Sale Price
A52-500-000 A52-515-046	Pocket Carbide S Carbide Refill	criber	6.0"	\$16.00 6.05	\$11.50
<	Heavy duty     Replaceat	ole carbide tip • Knurle	ed grip • Poc	ket clip     • Ma	gnetic end cap
Order Number	Description		Overall Length	List Price	Sale Price
A52-500-080 A52-500-085	Replaceable Tip Carbide Carbide Refill	e w/magnetic end cap	5.75"	\$8.60 1.75	\$5.75
	Heavy duty	Fixed carbide tip	• Pencil-lik	ke design	Pocket clip
Order Number	Description	Overall Ler	ngth	List Price	Sale Price
A52-500-090	Fixed Tip Scriber		6.0"	\$5.80	\$3.50

46


# **Combination Squares**

- Blades are chrome plated, fully hardened and tempered, graduated in 8ths, 16ths, 32nds and 64ths
- Finished in black enamel
- · Square head has level and scriber point
- Double indexed protractor is graduated 180° in both directions



Order Number	Description	List Price	Sale Price
A52-373-012	Square Head with 12" blade	\$82.50	\$73.00
A52-386-006	Square and Center Head with 6" blade	11200	50.00
A52-370-012	Square, Protractor and Center Head with 12" blade	165.90	129.80

# **Cylindrical Squares**



- Hardened and the ends are lapped to 90° angular accuracy
- · 6" cylindrical squares: ±.0001"
- 12" cylindrical square: ±.00015"

Order Number	Description	List Price	Sale Price
A52-750-006	NEW 6" cylindrical square	\$175.00	\$160.00
A52-750-012	<b>NEW</b> 12" cylindrical square	250.00	230.00

### **Steel Squares & Sets**

 Made of the finest carbon tool steel, these economy squares have true right angles both inside and outside

- Beams and blades ground and lapped for straightness and parallelism
- Hardened blade
- · Beam grooved at inner corner for clearance of burrs and dirt

NEW!

- · Squareness of blade edge to the working face:
- 2" & 3" = ±.0006", 4" & 6" = ±.0008", 9" & 12" = ±.0012"

Blade Size Beam Size

1.5"

2.5"

3"

4"

6"

8"

2"

3"

4"

6"

9"

12"



Order Number	Size/Description	List Price	Sale Price
A52-432-444	3 Piece Square Set: 2", 4" & 6" with shop hardened case	\$52.00	\$47.75
A52-432-246	4 Piece Square Set: 2", 3", 4" & 6" with shop hardened case	61.90	53.95
A52-432-469	4 Piece Square Set: 4", 6", 9" & 12" with shop hardened case	103.95	102.75
A52-432-004	4" Square only	18.75	17.00
A52-432-006	6" Square only	20.80	18.25
A52-432-009	9" Square only	41.60	38.50
A52-432-012	12" Square only	70.75	64.50

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

Volume 1

A high quality precision instrument that uses the Rockwell A, B and C scales for measuring hardness. Featuring ease of operation, automatic loading and unloading, automatic holding of test force and an easy-to-read LCD.

### Features:

/olume 14.2

TOOL-A-THON

- · New, advanced, multi-function indicator readout
- Full color LED display
- · Built in hardness calculator statistics function
- Standards: EN-ISO 6508 and ASTM-E18
- Resolution: .02 of a Rockwell unit
- Test loads: 10 kgf preload/60, 100, 150 kgf load
- Rockwell scales: A, B, C, F
- Testing space: Vertical = 6.7"/170mm,

Horizontal = 6.5"/165mm (from centerline)

### Accessories included:

- Diamond Rockwell indentor
- Rockwell ball indentor 1/16"
- ±60HRC Hardness test block
- ±25HRC Hardness test block
- ±85HRB Hardness test block
- Flat anvil 60mm ø
- · Large flat anvil 150mm ø
- V-anvil 40mm ø
- Adjustable feet
- · Protective spindle cover

Order Number	Description	List Price	Sale Price
A54-770-650-1	<b>NEW</b> Digital Rockwell Hardness Tester	\$5170.00	\$4653.00

NEW!

# **Analog Rockwell Hardness Tester**



A high quality precision instrument that uses the Rockwell A, B, C and F scales for measuring hardness. A reasonably priced solution for those requiring precision and durability.

### Features:

- · Standards: EN-ISO 6508 and ASTM-E18
- Resolution: .5 Rockwell unit
- Test loads: 10 kgf preload/60, 100, 150 kgf load
- · Rockwell scales: A, B, C, F
- Testing space: Vertical = 6.7"/170mm,

Horizontal = 6.5"/165mm (from centerline)

Fowler

### Accessories included:

- Diamond Rockwell indentor
- · Rockwell ball indentor 1/16"
- ±60HRC Hardness test block
- ±25HRC Hardness test block
  - ±85HRB Hardness test block
  - Flat anvil 60mm ø
  - Large flat anvil 150mm ø
  - V-anvil 40mm ø
- Adjustable feet
- Protective spindle cover



Order Number A53-770-600

 Imber
 Description
 List Price
 Sale Price

 600
 Analog Rockwell Hardness Tester
 \$2194.50
 \$1970.00



The X-Pro Portable Roughness Tester II can be used for many applications by selecting from a variety of accessories, including:

· Stand with swivel

· A variety of probes

For certain Applications, RS232 is available on certain models (contact the Fowler technical department for more information)



(X-Pro shown with optional stand with swivel.)

### X-Pro Portable Roughness Tester II

Order Number	Description	List Price	Sale Price
A54-410-500	Portable Surface Roughness Tester .0004" probe	\$1644.50	\$1500.00
A54-410-600	Portable Surface Roughness Tester .0002" probe	1644.50	1500.00

### X-Pro Portable Roughness Tester II Stand with Swivel

Order Number	Description	List Price
A54-400-896	Stand with Swivel Attachment	\$396.00

### X-Pro Portable Roughness Tester II Probes and Accessories

Order Number	Description	Resolution	List Price
A54-400-319	General Purpose Probe	.0004"	\$547.80
A54-400-326	General Purpose Probe	.0002"	547.80
A54-420-321	Small Bore Probe	.0004"	715.00
A54-420-327	Small Bore Probe	.0002"	715.00
A54-420-301	Traverse Chisel Probe	.0004"	715.00
A54-420-302	Parallel Chisel Probe	.0004"	715.00
A54-420-328	Groove Bottom Probe	.0004"	715.00
A54-420-120	AC Adapter Kit		60.50

olume 14.

49

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.



Prices & Specifications are subject to change without notice.

50



Its compact size and built-in illumination make our bore viewer fully portable. Combine that with stainless steel construction, a magnifying glass and inspection mirror, and you get a top quality internal inspection viewer that can be used anywhere in a wide variety of applications!

- Use for inspecting bores, cavities, threads, undercuts, raceways, surface finish, tools and intricate assemblies
- Views bores from 1/8" in diameter and up
- Stainless steel construction

NEW.

- · Mold makers-perfect for inspecting passages and cavities
- Maintenance-inspect many industrial problems on-site and avoid disassembly



Order Number	Description	List Price	Sale Price
A52-660-777	<b>NEW</b> Boreview Inspection Set	\$341.60	\$238.00

# FLEX CHROME KIT Combo Kit includes both.....

Disc & Rotor/Ball Joint Gage with Chrome Flex Arm



- Checks ball joint wear and disc rotor runout
- Checks tire and wheel runout, gear backlash, valve guide wear, etc.
- Corrosion resistant
- Chrome plated 12" flex arm
- Meets all state inspection requirements.
- Indicator features 0-1" travel and .001" graduation

Order Number
A52-520-451





**14 LED Flashlight** 

with Flex Bar Attachment

14 LED Ultra-Bright flashlight
 Quick release mounting bracket
 3 "AAA" batteries included

List Price

\$156.80

Everything packed in a convenient, shop-hardened case!

Description

Disc and Rotor Flex Chrome Kit

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

51

Sale Price

\$119.00



# QUICK RELEASE CAM!

# FAST & TIGHT!

# **CHANGE TAPS FAST!**

### Features:

- Fits wide range of tap sizes: 1/8" to 1/2" (M3 to M12)
- Patented Revolutionary Cam-Lock System
- · Quick-action clamping for easy replacement
- · Taps will never release during use
- · Heavy-duty design for reliability and long life
- Handles extreme torque
- · Can be used as a hand drill for sizes: 1/16" to 5/16"

### For instructional video

### search "Tap-X" at www.youtube.com

Order Number	Description	List Price	Sale Price
A52-492-350	Tap-X Cam-Locking Tap Wrench	\$50.00	\$30.00

FAST, CAM-LOCHING ACTION

CAM-LOCKING

INDI-	Indicating	Micro	meter	
Fowler	E = 0			]}
K-SERIES V V V V V V V V V V V V V V V V V V V		sion grou Fully insu- finish Wider Mi Carbide t Retractin in relation 0-1" Ran- Flatness: Dial grad Indicated	ulated frame, sati cro-Fine graduati tipped anvil & spi g button conveni n to operator's ha ge, head graduat :.000012" luated in .00005" l accuracy of .000 of spindle: .256"	n chrome ons ndle ently located nd ed in .001"
Order Number	Description			Sale Price
Order Number A52-245-501	Description 0-1" Indi-X Indicating Micrometer		List Price \$291,20	Sale Price \$245.00



52

Wyler Clinotronic Plus is an electronic level with unsurpassed versatility. It is economically priced, uses a specially designed microprocessor and the well-proven WYLER inclination sensor. Features: • Range of ±45°, capacity of 0-360° • Resolution of 0.01° (selectable) • Adjustable base length • Built-in calibration program • Uses standard 1.5v AA batteries • Desired units to be selected by push button command • Display: use any units common to inclina- tion measurements • Absolute or relative measuring mode selectable by push button	Clinotronic PLUS + Clinotronic P	
Seal-tec technology for excellent perfor- mance even in difficult environmental conditions     Interface connection RS232 is integrated. Special purpose		s Quality!
Seal-tec technology for excellent perfor- mance even in difficult environmental conditions     Interface connection RS232 is integrated. Special purpose cables available	DIRECT	
Seal-tec technology for excellent perfor- mance even in difficult environmental conditions     Interface connection RS232 is integrated. Special purpose cables available     Low battery indication	The following measuring units n selected:	
Seal-tec technology for excellent perfor- mance even in difficult environmental conditions     Interface connection RS232 is integrated. Special purpose cables available	The following measuring units n	nay be
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> </ul>	The following measuring units n selected: Deg/Arcmin Arcmin / Arcsec	nay be 00° 00' 00' 00"
Seal-tec technology for excellent perfor- mance even in difficult environmental conditions     Interface connection RS232 is integrated. Special purpose cables available     Low battery indication     No loss of calibration data by power failure     Price includes fitted case     Technical Specifications:	The following measuring units n selected: Deg/Arcmin Arcmin / Arcsec GON / Neugrad (2 Dec) 00	nay be 00° 00' 00' 00" .00 gon
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:</li> <li>Measuring range/capacity: ± 45°/0-360°</li> </ul>	The following measuring units n           selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00	nay be 00° 00' 00' 00" 000 gon 000 gon
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ±45°/0-360°</li> <li>Response time: value available within 5 seconds</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         00.00	nay be 00° 00' 00' 00" 000 gon 000 gon 0 mm/m
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;01°</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         00.00           mm / rel.Basis (4 Dec)         .000	nay be 00° 00' 00' 00" 0.00 gon 000 gon 0 mm/m 0 mm/m
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;01°</li> </ul> </li> </ul>	The following measuring units n           selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         00.00           mm / rel.Basis (4 Dec)         .0000           Inch / rel.Basis (4 Dec)         .0000	nay be 00° 00' 00' 00" 1.00 gon 000 gon 0 mm/m 0 mm/m 100"/10"
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ±45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;.01°</li> <li>Linearity: within 3 min. of arc</li> <li>Temp. coefficient: less than 0.01°/°C</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Aremin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         0.000           mm / rel.Basis (4 Dec)         .0000           Inch / rel.Basis (4 Dec)         .000           Inch / rel.Basis (4 Dec)         .000	nay be 00° 00' 00' 00'' .00 gon 000 gon 0 mm/m 000''/10'' 0000
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;01°</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         0.000           Inch / rel.Basis (4 Dec)         .0000           Inch / rel.Basis (4 Dec)         .0000           mm / m (2 Dec)         0.000	nay be           00° 00'           00' 00"           .00 gon           00 mm/m           0 mm/m           000"/10"           0000           00m/m
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;.01°</li> <li>Linearity: within 3 min. of arc</li> <li>Temp. coefficient: less than 0.01°/°C</li> <li>Data output: Serial</li> <li>Battery: Standard AA 1.5V alkaline/130hrs or AA 3.0V Mn02-Lithium (for longer operation 300/hrs)</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         0000           Inch / rel.Basis (4 Dec)         .000           Inch / rel.Basis (4 Dec)         .000           artillery per mille A‰         mm / m (2 Dec)         00.00           Inch / 10 Inches         .000	nay be 00° 00' 00' 00'' .00 gon 000 gon 0 mm/m 000''/10'' 0000
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;01°</li> <li>Linearity: within 3 min. of arc</li> <li>Temp. coefficient: less than 0.01°/°C</li> <li>Data output: Serial</li> <li>Battery: Standard AA 1.5V alkaline/130hrs or AA 3.0V Mn02-Lithium (for longer operation 300/hrs)</li> <li>Housing: aluminum hard anodized.</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         .00           mm / rel.Basis (2 Dec)         0.000           Inch / rel.Basis (4 Dec)         .000           Inch / rel.Basis (4 Dec)         .000           Intillery per mille A‰         mm / m (2 Dec)         00.00           Inch / 10 Inches         .000	nay be 00° 00' 00 00'' 1.00 gon 0 mm/m 000''/10'' 0000' 0 mm/m 000''/10'' 000''/12''
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;.01°</li> <li>Linearity: within 3 min. of arc</li> <li>Temp. coefficient: less than 0.01°/C</li> <li>Data output: Serial</li> <li>Battery: Standard AA 1.5V alkaline/130hrs or AA 3.0V Mn02-Lithium (for longer operation 300/hrs)</li> <li>Housing: aluminum hard anodized.</li> <li>Dimensions: 4 x 3 x 1"(100 x 75 x 30mm)</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         000           mm / rel.Basis (2 Dec)         0000           Inch / rel.Basis (4 Dec)         0000           Inch / rel.Basis (4 Dec)         0000           Inch / rel.Basis (4 Dec)         0000           Inch / 10 Inches         0000           Inch / 12 Inches         0000           Milliradian         00.00 mrade	nay be 00° 00' 00 00'' 1.00 gon 0 mm/m 000''/10'' 0000' 0 mm/m 000''/10'' 000''/12''
<ul> <li>Seal-tec technology for excellent performance even in difficult environmental conditions</li> <li>Interface connection RS232 is integrated. Special purpose cables available</li> <li>Low battery indication</li> <li>No loss of calibration data by power failure</li> <li>Price includes fitted case</li> <li>Technical Specifications:         <ul> <li>Measuring range/capacity: ± 45°/0-360°</li> <li>Response time: value available within 5 seconds</li> <li>Repeatability: &lt;01°</li> <li>Linearity: within 3 min. of arc</li> <li>Temp. coefficient: less than 0.01°/°C</li> <li>Data output: Serial</li> <li>Battery: Standard AA 1.5V alkaline/130hrs or AA 3.0V Mn02-Lithium (for longer operation 300/hrs)</li> <li>Housing: aluminum hard anodized.</li> </ul> </li> </ul>	The following measuring units in selected:           Deg/Arcmin           Arcmin / Arcsec           GON / Neugrad (2 Dec)         00           GON / Neugrad (4 Dec)         000           mm / rel.Basis (2 Dec)         0000           Inch / rel.Basis (4 Dec)         0000           Inch / rel.Basis (4 Dec)         0000           Inch / rel.Basis (4 Dec)         0000           Inch / 10 Inches         0000           Inch / 12 Inches         0000           Milliradian         00.00 mrade	nay be 00° 00' 00 gon 00 gon 0 mm/m 000''/10'' 0000' 0 mm/m 000''/10'' 0000''/12'' I (2Dec)

### A54-635-610 Replacement Battery 44.00 Wyler Magnetic Precision Spirit Level

Description

Clinotronic Plus


WYLER Universal Spirit Levels feature an insulated handle. Main vial unit observed from above and from either side. The vial unit is set into a steel tube in a stress free location, and can be adjusted in the body of the Spirit Level by a fine thread and screw system. Hand scraped by Swiss craftsmen. Includes fitted case.

### Features:

Order Number

A54-635-601

WYLER Magnetic Precision Spirit Level checks and levels cylinders, horizontal and vertical surfaces. Constructed with two prismatic measuring surfaces. Sensitivity .0002" per 10". Magnets to ensure complete adherence to vertical surfaces of parts and vertical arbors or shafts. Operators on milling and boring units, inspectors and fitters work with free hands.



List Price

\$1875.00

Sale Price

NEW!

\$1675.00

Be sure to use the "A" prefix when ordering Tool-A-Thon specials.

Volume 14.

TOOL-A-THO

### **Trimos V-Series Height Gages** Versatility, Reliability, Durability

Combining a sleek ultra-modern design, robust construction, userfriendly interface, 5-year warranty and exceptional value, the Fowler/ Trimos V-series is the ideal electronic multifunction height gage for your quality control or workshop environment.

Unlike some of our competitor's height gages that require expensive accessories, the V comes fully equipped to handle ID, OD, centerline, MIN/ MAX and TIR measurements.

**NO EXPENSIVE ACCESSORIES REQUIRED!** 

057690

All Price

Specifications: Measuring range

Application range

Max. resolution

Repeatability (2s) Max. displacement speed

Measuring force

23

ise Qualify

54

Data output

Accuracy

12"/300mm 24"/600mm 21"/535mm 32"/835mm .0002"/5µm .00028"/7µm Squareness deviation (in measuring direction) .00039"/10µm .00059"/15µm .00005"/.001mm .00008"/2µm (Ø.00016"/4µm) 1.5 m/s 1N **RS-232** 




A-THON BEST SELLER!

OWLER HIGH

Order Number	Description	List Price
A54-191-014-1	0-12"/300mm Trimos V	\$4250.00
A54-191-024-1	0-24"/600mm Trimos V	\$4950.00

### **Trimos V Plus Series Height Gages** Versatility, Reliability, Durability



The ideal shop or lab gage. Very accurate and very easy to use for all everyday manufacturing applications.

		II Price		
	Specifications:			
	Measuring range	12"/300mm	24"/600mm	40"/1000mm
and the second se		21"/535mm	32.8"/835mm	48.6"/1235
78655	Application range			
67	Application range Accuracy		2.5 + L(mm)/300	
				.00047"/.012mr
	Accuracy			
8	Accuracy Squareness deviation (in measuring direction)		.00032"/.008mm	01/.01mm)
	Accuracy Squareness deviation (in measuring direction) Max. resolution		.00032"/.008mm .00005"/.0005"(.0	01/.01mm)
	Accuracy Squareness deviation (in measuring direction) Max. resolution Repeatability (2s)		.00032"/.008mm .00005"/.0005"(.0 .00008"/.002	01/.01mm) mm

Order Number	Description	List Price
A54-199-300	12"/300mm Trimos V Plus	\$5800.00
A54-199-024	24"/600mm Trimos V Plus	7500.00
A54-199-040	40"/1000mm Trimos V <mark>Plus</mark>	10,700.00

TOOL-A-THON

# Fowler TOOL-A-THON

# **Fowler Mobile Tech Center**



**E** Follow us on Twitter @ Fowler\_MTC



# Fowler's Newest & Most Popular Precision Tools and Technologies are on the road and going across the country in Fowler's NEW Mobile Tech Center!

For details and information about getting the Fowler Mobile Tech Center to your location, contact the Vice President of Sales, Jeff Petersen, at jeffp@fvfowler.com

Volume 14.2



www.fvfowler.com





Fowler High Precision





FowlerVid